

H 14

GRUBER
KEG-ANLAGEN



WWW.KEG-GRUBER.AT



ALFRED GRUBER Gesellschaft m. b. H.
Nordstraße 6, 5301 Eugendorf, Österreich / Austria

Telefon: 0043/062 25/71 60 | E-Mail: office@keg-gruber.at | Web: www.keg-gruber.at



HALBAUTOMATISCHER FLASCHENREINIGER

HAUPTMERKMALE:

- Leistung(en): 6/11/17 Reinigungszyklen/h
25 Spritzstellen für Flasche ø70mm (0,5l)
16 Spritzstellen für Flasche ø85mm
9 Spritzstellen für Flasche ø140mm (2l)
8 Spritzstellen für Flasche ø160mm
- für Flaschen Innen- und Außenreinigung
- für alle handelsüblichen Flaschen
- maximale Flaschenhöhe = 320mm
- Frontmodell mit ausziehbarem Einsatz

MASCHINE:

- komplett aus Edelstahl (Werkstoff 1.4301)
- integrierter Tank, ca. 10.8 Liter
- außenliegende Tankheizung
- integrierter Heißwasserboiler, ca. 8 Liter
- automatische Nachdosierung des Reinigungsmittels direkt in den Tank, Dosiermenge einstellbar
- automatische Nachdosierung, Dosiermenge einstellbar
- permanente Laugereinigung über entfernbaren Siebfiltereinsatz
- Reinigungseinsatz auf Rollen mit Schiebekupplung
- Schlauchpumpen für Reinigungsmittel und Klarspüler
- drei Reinigungsprogramme
- rotierende Wascharme mit Spritzdüsen für die Außenreinigung der Flaschen
- doppelwandige, isolierte Tür
- Reinigungszeiten und Temperaturen leicht einstellbar
- Fehleranzeige mit Fehlercode
- Sicherheitsschalter an der Fronttür
- Einhand-Bedienung

OPTIONEN:

- mit eingebauter Wasserenthärtung
- mit Dampfspülung
- mit fahrbarem Untergestell (inklusive Bodentasse für Reinigungsmittelkanister)

REINIGUNGSPROGRAMM:

Hauptspülung mit Lauge 60°C aus dem Tank
Entleerung
Nachspülung mit Heißwasser 85°C
Entleerung
Ende

technische Änderungen vorbehalten !

SEMI AUTOMATIC BOTTLE-CLEANING MACHINE

FEATURES:

- capacity: 6/11/17 cleaning cycles/h
25 nozzles for bottle ø70mm (0,5l)
16 nozzles for bottle ø85mm
9 nozzles for bottle ø140mm (2l)
8 nozzles for bottle ø160mm
- for bottle inside and outside cleaning
- applicable for bottles customary in the trade
- height maximum 320mm
- front model with extensile bottle insert

MACHINE:

- completely in stainless steel AISI 304
- one integrated tank, approx. 10.8 liters
- heating element outside of the tank
- integrated boiler for hot water, 8 liters
- automatic dosage of the cleaning agent directly into the tank, dosage of cleaning agent adjustable
- automatic dosage of the rinse aid, dosage adjustable
- permanent filtering of the tank by a removable strainer
- bottle cleaning insert mounted on rolls, with slide coupling
- hose pump for cleaning agent and rinse aid
- three cleaning programs
- rotating wash arms with spraying nozzles for bottle outside cleaning
- double wall front door, isolated
- times and temperatures for cleaning process easy adjustable
- indication of malfunction with error code
- front door with safety switch
- one hand operation

OPTIONS:

- with build-in water softening
- with steam rinsing
- with mobile underframe (incl. tray for cleaning agent)

CLEANING PROGRAM:

main cleaning cycle (lye 60°C) via tank
emptying (remainders are dripping down)
hot water post-rinsing 85°C
emptying (remainders are dripping down)
end of program

technical changes reserved !