

# MiniKEG F / EF / KF



WWW.KEG-GRUBER.AT



MiniKEG KF



MiniKEG F / EF

**ALFRED GRUBER Gesellschaft m. b. H.**  
Nordstraße 6, 5301 Eugendorf, Österreich / Austria

Telefon: 0043/062 25/71 60 | E-Mail: [office@keg-gruber.at](mailto:office@keg-gruber.at) | Web: [www.keg-gruber.at](http://www.keg-gruber.at)



## HALBAUTOMATISCHE KEG-FÜLLANLAGE

### AUSSTATTUNGSVARIANTEN:

#### **MiniKEG F** nur für

- Edelstahl Keg

#### **MiniKEG EF**

- Edelstahl Keg
- Einweg Keg ohne Inlay  
Dolium, PolyKEG, Petainer,...

#### **MiniKEG KF**

- Edelstahl Keg
- Keg mit Inlay wie auch ohne Inlay  
Dolium, PolyKEG, Petainer, KeyKeg,  
EcoDraft,...

### HAUPTMERKMALE:

- Leistung 50-60 Keg/h
- für Keg-Füllung
- für alle Edelstahl Keg und EinwegKeg's
- für alle handelsüblichen Fittingsysteme
- alle Parameter und Zeiten verstellbar
- geringe Sauerstoffaufnahme

### MASCHINE:

- komplett aus Edelstahl (min. 1.4301)
- Schaltschrank komplett aus Edelstahl
- 7 Füllmengen speicherbar (F-IDM / KF)
- ein Füllkopf mit Fixverrohrung
- Kontrolleinrichtungen für Fassventil offen
- Füllerregelung über Abluftdrucksteuerung
- zwei Abluftventile optimalen Füllvorgang
- Füllkontrolle mittels Differenzdruck
- Umschraubpanel an der Maschinenfront
- Reinigungsadapter für CIP-Reinigung

### STEUERUNG:

- Siemens SPS-Steuerung
- automatische Co2 Druck Anpassung
- Digitales Textdisplay zur Schrittanzeige
- Festo Multipol-Pneumatik-Ventilinsel
- Zweihand Start

technische Änderungen vorbehalten !

## SEMI AUTOMATIC KEG-FILLING MACHINE

### EQUIPMENT VARIATIONS:

#### **MiniKEG F** only for

- stainless steel Keg

#### **MiniKEG EF**

- stainless steel Keg
- Keg without bag system  
Dolium, PolyKEG, Petainer,...

#### **MiniKEG KF**

- stainless steel Keg
- Keg with bag as well as without bag  
Dolium, PolyKEG, Petainer, KeyKeg,  
EcoDraft,...

### FEATURES:

- capacity 50-60 keg/h
- for keg filling
- for all s/s kegs and One Way Keg
- for all fitting types
- all parameter and times adjustable
- little absorption of oxygen during filling

### MACHINE:

- completely in stainless steel (AISI 304)
- switch cabinet completely in stainless steel
- leakage area flushing
- one filling head with fix piping
- control for keg-valve opened
- filling with pressure control of vent air
- two vent valves for best filling result
- filling control with pressure transformer
- pipe panel at the front
- adapter for CIP cleaning

### CONTROL:

- control unit made of Siemens
- automatic Co2 pressure equalizing
- text display to indicate program step
- multipole valve block made of Festo
- two-hand start

technical changes reserved !